

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Section 1: Identification

Product name : LACQUER SPRAY CLEAR HIGH GLOSS

Product code : 0893 351 930

Manufacturer or supplier's details

Company : Wurth NewZealand Ltd

Address : 99 McLauglins Road
Wiri, Auckland 2104

Telephone : +64 9 262 3040

Emergency telephone number : 0800 764 766

E-mail address : prodsafe@wuerth.com

Telefax : +64 9 262 3030

Recommended use of the chemical and restrictions on use

Recommended use : Paints

Section 2: Hazard identification**GHS Classification**

Aerosols : Category 1

Serious eye damage/eye irritation : Category 2

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms :



LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
 Date of first issue: 21.05.2012

Components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 30 -< 60
Propane	74-98-6	>= 10 -< 20
Butane	106-97-8	< 10
n-Butyl acetate	123-86-4	< 10
Isobutane	75-28-5	< 10
2-Methoxy-1-methylethyl acetate	108-65-6	< 10
Xylene	1330-20-7	>= 1 -< 10
Ethanol	64-17-5	< 10
Butanone	78-93-3	< 10
Butyl glycollate	7397-62-8	>= 1 -< 3
Ethylbenzene	100-41-4	>= 1 -< 10

Section 4: First-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
 Remove contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
 If easy to do, remove contact lens, if worn.
 Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Prolonged or repeated contact may dry skin and cause irritation.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Notes to physician : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : 2YE
-

Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate contain-

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7: Handling and storage

- | | | |
|-----------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight. |
| Materials to avoid | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents |

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Flammable liquids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Explosives

Recommended storage temperature : < 40 °C

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	WES-TWA	500 ppm 1,185 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		WES-STEL	1,000 ppm 2,375 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butane	106-97-8	WES-TWA	800 ppm 1,900 mg/m ³	NZ OEL
		STEL	1,000 ppm	ACGIH
n-Butyl acetate	123-86-4	WES-STEL	200 ppm 950 mg/m ³	NZ OEL
		WES-TWA	150 ppm 713 mg/m ³	NZ OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
Xylene	1330-20-7	WES-TWA	50 ppm 217 mg/m ³	NZ OEL
		TWA	20 ppm	ACGIH
Ethanol	64-17-5	WES-TWA	1,000 ppm 1,880 mg/m ³	NZ OEL
		STEL	1,000 ppm	ACGIH
Butanone	78-93-3	WES-STEL	300 ppm 890 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		WES-TWA	150 ppm 445 mg/m ³	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Ethylbenzene	100-41-4	WES-TWA	100 ppm	NZ OEL

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
 Date of first issue: 21.05.2012

			434 mg/m ³	
		WES-STEL	125 ppm 543 mg/m ³	NZ OEL
		TWA	20 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift	50 mg/l	NZ BEI
		Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acids	Urine	End of exposure or end of shift	0.25 g/g creatinine	NZ BEI
		Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
Butanone	78-93-3	MEK	Urine	End of shift	2 mg/l	NZ BEI
		methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Xylene	1330-20-7	Methylhippuric acid	Urine	End of shift	1.5 g/l	NZ BEI
		Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

Engineering measures

- : Minimize workplace exposure concentrations.
- If sufficient ventilation is unavailable, use with local exhaust ventilation.
- If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust venti-

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

lation.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : butyl-rubber
- Break through time : < 15 min
- Glove thickness : 0.7 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Section 9: Physical and chemical properties

- Appearance : aerosol
- Propellant : Butane, Isobutane, Propane
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : substance/mixture is non-polar/aprotic

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Melting point/freezing point : Decomposes before melting.

Initial boiling point and boiling range : Not applicable

Flash point : < 0 °C
Method: DIN 51755 Part 2, closed cup
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 13.0 %(V)

Lower explosion limit / Lower flammability limit : 1.7 %(V)

Vapour pressure : 3,600 hPa (20 °C)

Relative vapour density : Not applicable

Relative density : 0.8 (23 °C)
Reference substance: Water

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 365 °C

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Possibility of hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

Section 11: Toxicological information

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Acetone:**

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm
Exposure time: 15 min
Test atmosphere: gas

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Exposure time: 4 h
Test atmosphere: vapour

n-Butyl acetate:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Isobutane:

- Acute inhalation toxicity : LC50 (Mouse): 260200 ppm
Exposure time: 4 h
Test atmosphere: gas

2-Methoxy-1-methylethyl acetate:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC0 (Rat): 9.48 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Xylene:

- Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.
- Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapour
- Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Ethanol:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Butanone:

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Butyl glycollate:

Acute oral toxicity : LD50 (Rat): 4,595 mg/kg

Acute inhalation toxicity : LC0 (Rat): >= 6.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No skin irritation

Xylene:

Species : Rabbit
Result : Skin irritation

Ethanol:

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Butyl glycollate:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Acetone:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

n-Butyl acetate:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No eye irritation

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Ethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Butanone:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Butyl glycollate:

Species : Rabbit
Result : Irreversible effects on the eye

Ethylbenzene:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Acetone:**

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

n-Butyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

2-Methoxy-1-methylethyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Ethanol:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Butanone:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Butyl glycollate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: equivocal

Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Butyl glycollate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Mouse Lymphoma
Method: OECD Test Guideline 476
Result: negative

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:**Acetone:**

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

2-Methoxy-1-methylethyl acetate:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Ethylbenzene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assess- : Limited evidence of carcinogenicity in animal studies

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.
Remarks: Based on national or regional regulation.

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Species: Mouse
Application Route: Ingestion
Result: negative

Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Butyl glycollate:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.
Remarks: Based on national or regional regulation.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**Acetone:**

Assessment : May cause drowsiness or dizziness.

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Propane:

Assessment : May cause drowsiness or dizziness.

Butane:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Isobutane:

Assessment : May cause drowsiness or dizziness.

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Butanone:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:**Xylene:**

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Butanone:

Assessment : May cause damage to organs through prolonged or repeated exposure.
Remarks : Based on national or regional regulation.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Acetone:**

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapour)
Exposure time : 8 Weeks

Propane:

Species : Rat
NOAEL : 7.214 mg/l
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Butane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

Isobutane:

Species : Rat
NOAEL : 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

2-Methoxy-1-methylethyl acetate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days
Method : OECD Test Guideline 422

Species : Mouse
NOAEL : 1.62 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr
Remarks : Based on data from similar materials

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Species : Rabbit
NOAEL : > 1,838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days
Remarks : Based on data from similar materials

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethanol:

Species : Rat
NOAEL : 1,280 mg/kg
LOAEL : 3,156 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Butanone:

Species : Rat
NOAEL : 14.84 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

Butyl glycollate:

Species : Rat
NOAEL : 1,000 mg/kg
Application Route : Ingestion
Exposure time : 29 Days
Method : OECD Test Guideline 407

Ethylbenzene:

Species : Rat
LOAEL : 0.868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Section 12: Ecological information

Ecotoxicity

Components:

Acetone:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (Daphnia magna (Water flea)): \geq 79 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |
| Toxicity to microorganisms | : | EC50: 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192 |

n-Butyl acetate:

- | | | |
|-------------------------------|---|---|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other | : | EC50 (Daphnia sp. (water flea)): 44 mg/l |

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): > 1,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.6 mg/l
Exposure time: 9 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6,500 mg/l
Exposure time: 16 h

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Butyl glycollate:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): >= 50 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 280 mg/l
Exposure time: 24 h
Method: DIN 38412

Toxicity to algae/aquatic plants : EC10 (Lemna gibba (gibbous duckweed)): > 87.4 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 2,320 mg/l
Exposure time: 18 h

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Persistence and degradability**Components:****Acetone:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Propane:

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

Butane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Isobutane:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 385.5 h
Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Butanone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Butyl glycollate:

Biodegradability : Result: Readily biodegradable.

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Bioaccumulative potential**Components:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.31

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.8

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1.2

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.6

LACQUER SPRAY CLEAR HIGH GLOSS

Version 9.1 Revision Date: 02.02.2023 SDS Number: 10656895-00011 Date of last issue: 20.09.2022
Date of first issue: 21.05.2012

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)
-

Section 14: Transport information**International Regulations****UNRTDG**

- UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

- UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

- UN number : UN 1950
Proper shipping name : AEROSOLS
- Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no
-

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**NZS 5433**

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
Hazchem Code	:	2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****HSNO Approval Number**

HSR002517 Aerosols Flammable Carcinogenic Group Standard

HSW Controls

Certified handler certificate not required.
Tracking hazardous substance not required.
Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

Section 16: Other information

Revision Date : 02.02.2023

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NZ BEI	:	New Zealand. Biological Exposure Indices
NZ OEL	:	New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

LACQUER SPRAY CLEAR HIGH GLOSS

Version	Revision Date:	SDS Number:	Date of last issue: 20.09.2022
9.1	02.02.2023	10656895-00011	Date of first issue: 21.05.2012

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NZ OEL / WES-TWA	:	Workplace Exposure Standard - Time Weighted average
NZ OEL / WES-STEL	:	Workplace Exposure Standard - Short-Term Exposure Limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN