

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	STAINLESS STEEL SPRAY PERFECT - 400 ML
Product code	:	0893114116
Unique Formula Identifier (UFI)	:	YF00-Q072-R00G-46CK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Solvent-borne coatings, Compressed Gas (Aerosol cans) Professional use product
-------------------------------	---	---

Recommended restrictions on use	:	Not applicable
---------------------------------	---	----------------

1.3 Details of the supplier of the safety data sheet

Company	:	Wurth UK Ltd 1 Centurion Way Erith, Kent
Telephone	:	+44 (0)3300 555 444
Telefax	:	+44 (0)3300 555 666
E-mail address of person responsible for the SDS	:	prodsafe@wuerth.com

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex-	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing spray.
- P264 Wash skin thoroughly after handling.

Storage:

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

- Dimethyl ether
- n-Butyl acetate
- Acetone
- Ethyl acetate

Additional Labelling

- EUH208 Contains Nickel.
May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 50 - < 70
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10
Xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2.5 - < 10
Ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10
Ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2.5 - < 10
Butan-1-ol	71-36-3 200-751-6 603-004-00-6	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336	>= 1 - < 3
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	Asp. Tox. 1; H304	>= 1 - < 10

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Nickel	7440-02-0 231-111-4 028-002-01-4	Skin Sens. 1; H317 Carc. 2; H351 STOT RE 1; H372 (Respiratory Tract) Aquatic Chronic 3; H412	>= 0.25 - < 1
Substances with a workplace exposure limit :			
Chromium	7440-47-3 231-157-5		>= 1 - < 10
Aluminium	7429-90-5 231-072-3 013-002-00-1	Flam. Sol. 1; H228 Water-react. 2; H261	>= 1 - < 10
Molybdenum	7439-98-7 231-107-2		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Causes serious eye irritation.
May cause drowsiness or dizziness.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides
Chromium compounds
Nitrogen oxides (NO_x)
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0	Revision Date: 30.04.2023	SDS Number: 9701550-00006	Date of last issue: 26.01.2023 Date of first issue: 21.12.2009
-----------------	------------------------------	------------------------------	---

Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
If spillage enters rivers or watercourses, inform the Environment Agency (emergency telephone number 0800 807060).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Do not breathe decomposition products.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases

Recommended storage temperature : < 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m ³	GB EH40
		STEL	500 ppm 958 mg/m ³	GB EH40
		TWA	1,000 ppm 1,920 mg/m ³	2000/39/EC
Further information: Indicative				
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
Further information: Indicative				
Xylene	1330-20-7	TWA	50 ppm 220 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL	100 ppm 441 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
Ethyl acetate	141-78-6	STEL	400 ppm 1,468 mg/m ³	GB EH40
		TWA	200 ppm 734 mg/m ³	GB EH40
		TWA	200 ppm 734 mg/m ³	2017/164/EU
Further information: Indicative				
		STEL	400 ppm 1,468 mg/m ³	2017/164/EU
Further information: Indicative				
Acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	GB EH40
		STEL	1,500 ppm 3,620 mg/m ³	GB EH40
		TWA	500 ppm 1,210 mg/m ³	2000/39/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

	Further information: Indicative			
Ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	125 ppm 552 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Chromium	7440-47-3	TWA	0.5 mg/m3	GB EH40
		TWA	2 mg/m3 (chromium)	2006/15/EC
	Further information: Indicative			
Aluminium	7429-90-5	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
Molybdenum	7439-98-7	TWA	10 mg/m3 (Molybdenum)	GB EH40
		STEL	20 mg/m3 (Molybdenum)	GB EH40
Nickel	7440-02-0	TWA	0.5 mg/m3 (Nickel)	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Capable of causing occupational asthma., Capable of causing cancer and/or heritable genetic damage.			
		TWA (Respirable dust)	0.01 mg/m3	2004/37/EC
	Further information: dermal and respiratory sensitisation, Carcinogens or mutagens			
		TWA (inhalable fraction)	0.1 mg/m3	2004/37/EC
	Further information: dermal and respiratory sensitisation, Carcinogens or mutagens			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Formaldehyde	50-00-0	TWA	2 ppm 2.5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		STEL	2 ppm 2.5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA	0.3 ppm 0.37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0.6 ppm 0.74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
Methanol	67-56-1	TWA	200 ppm 266 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	200 ppm 260 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m ³
	Workers	Inhalation	Acute systemic effects	1468 mg/m ³
	Workers	Inhalation	Long-term local effects	734 mg/m ³
	Workers	Inhalation	Acute local effects	1468 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

	Consumers	Inhalation	Long-term systemic effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic effects	734 mg/m ³
	Consumers	Inhalation	Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute local effects	734 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4.5 mg/kg bw/day
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Workers	Inhalation	Acute local effects	293 mg/m ³
	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	1.6 mg/kg bw/day
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Inhalation	Acute local effects	2420 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12.5 mg/kg bw/day
Dimethyl ether	Workers	Inhalation	Long-term systemic	1894 mg/m ³

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

	Consumers	Inhalation	effects	
	Consumers	Inhalation	Long-term systemic effects	471 mg/m ³
Chromium	Workers	Inhalation	Long-term local effects	0.5 mg/m ³
	Consumers	Inhalation	Long-term local effects	0.027 mg/m ³
Nickel	Workers	Inhalation	Long-term systemic effects	0.05 mg/m ³
	Workers	Inhalation	Acute systemic effects	680 mg/m ³
	Workers	Inhalation	Long-term local effects	0.05 mg/m ³
	Workers	Inhalation	Acute local effects	4 mg/m ³
	Workers	Skin contact	Long-term local effects	0.07 mg/cm ²
	Consumers	Inhalation	Long-term systemic effects	0.02 µg/m ³
	Consumers	Inhalation	Acute systemic effects	408 mg/m ³
	Consumers	Inhalation	Long-term local effects	0.02 µg/m ³
	Consumers	Inhalation	Acute local effects	2.4 mg/m ³
	Consumers	Skin contact	Long-term local effects	0.07 mg/cm ²
	Consumers	Ingestion	Long-term systemic effects	0.02 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0.012 mg/kg bw/day
Molybdenum	Workers	Inhalation	Long-term systemic effects	11.17 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	3.33 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3.4 mg/kg bw/day
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m ³
	Consumers	Inhalation	Long-term local effects	35.7 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef-	11 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

			fects	bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	55 mg/m ³
Aluminium	Workers	Inhalation	Long-term local effects	3.72 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3.95 mg/kg bw/day
Iron	Workers	Inhalation	Long-term local effects	3 mg/m ³
	Consumers	Inhalation	Long-term local effects	1.5 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	0.71 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Intermittent use/release	1.65 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1.15 mg/kg dry weight (d.w.)
	Marine sediment	0.115 mg/kg dry weight (d.w.)
	Soil	0.148 mg/kg dry weight (d.w.)
Ethylbenzene	Oral (Secondary Poisoning)	200 mg/kg food
	Fresh water	0.1 mg/l
	Freshwater - intermittent	0.1 mg/l
	Marine water	0.01 mg/l
	Sewage treatment plant	9.6 mg/l
	Fresh water sediment	13.7 mg/kg dry weight (d.w.)
	Marine sediment	1.37 mg/kg dry weight (d.w.)
Acetone	Soil	2.68 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food
	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.4 mg/kg dry weight (d.w.)
	Marine sediment	3.04 mg/kg dry weight (d.w.)
	Soil	29.5 mg/kg dry weight (d.w.)
Xylene	Fresh water	0.327 mg/l
	Intermittent use/release	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage treatment plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Soil	2.31 mg/kg dry weight (d.w.)
Dimethyl ether	Fresh water	0.155 mg/l
	Marine water	0.016 mg/l
	Intermittent use/release	1.549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0.681 mg/kg dry weight (d.w.)
	Marine sediment	0.069 mg/kg dry weight (d.w.)
	Soil	0.045 mg/kg dry weight (d.w.)
Chromium	Fresh water sediment	205.7 mg/kg
	Soil	21.1 mg/kg
	Fresh water	6.5 µg/l
Molybdenum	Fresh water	12.7 mg/l
	Marine water	2.28 mg/l
	Sewage treatment plant	21.7 mg/l
	Fresh water sediment	22600 mg/kg
	Marine sediment	2368 mg/kg
	Soil	9.9 mg/kg
n-Butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Sewage treatment plant	35.6 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Soil	0.09 mg/kg dry weight (d.w.)
Butan-1-ol	Fresh water	0.082 mg/l
	Marine water	0.008 mg/l
	Intermittent use/release	2.25 mg/l
	Sewage treatment plant	2476 mg/l
	Fresh water sediment	0.178 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

	Marine sediment	0.018 mg/kg
	Soil	0.015 mg/kg
Aluminium	Sewage treatment plant	20 mg/l

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to BS EN 166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Propellant	:	Dimethyl ether
Colour	:	silver
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-24 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	18.6 %(V)
Lower explosion limit / Lower flammability limit	:	3.0 %(V)
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

9.2 Other information

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde
Methanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Ethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 22.5 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Acetone:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Acute oral toxicity : LD50 (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7,426 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m³
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): \geq 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Nickel:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): 10.2 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Chromium:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Aluminium:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 0.888 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Molybdenum:

- Acute oral toxicity : LD50 (Rat): 2,689 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 3.92 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Product:

- Result : Skin irritation

Components:

n-Butyl acetate:

- Species : Rabbit

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Ethyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Butan-1-ol:

Species : Rabbit
Result : Skin irritation

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Nickel:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Chromium:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Aluminium:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Molybdenum:

Species : Rabbit

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

n-Butyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Ethyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Acetone:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Butan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Nickel:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Chromium:

Species : Rabbit

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Aluminium:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Molybdenum:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Butyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Ethyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Acetone:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Butan-1-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Nickel:

Assessment : Probability or evidence of skin sensitisation in humans

Chromium:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Aluminium:

Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Molybdenum:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Ethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Species: Hamster
Application Route: Ingestion
Result: negative

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Butan-1-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Chromium:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Aluminium:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Molybdenum:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Components:

Dimethyl ether:

Species	:	Rat
Application Route	:	inhalation (vapour)
Exposure time	:	2 Years
Result	:	negative

Xylene:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

Acetone:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	424 days
Result	:	negative

Ethylbenzene:

Species	:	Rat
Application Route	:	inhalation (vapour)
Exposure time	:	104 weeks
Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	:	Rat
Application Route	:	inhalation (vapour)
Exposure time	:	105 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Carcinogenicity - Assessment	:	Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------	---	--

Nickel:

Carcinogenicity - Assessment	:	Limited evidence of carcinogenicity in inhalation studies with animals.
------------------------------	---	---

Chromium:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	2 Years
Result	:	negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Remarks : Based on data from similar materials

Aluminium:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 86 weeks
Result : negative

Molybdenum:

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 105 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

ment
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Ethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal develop-
ment : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal develop-
ment : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal develop-
ment : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Nickel:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative
Remarks: Based on data from similar materials

Chromium:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Aluminium:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0	Revision Date: 30.04.2023	SDS Number: 9701550-00006	Date of last issue: 26.01.2023 Date of first issue: 21.12.2009
-----------------	------------------------------	------------------------------	---

Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative

Molybdenum:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Ethyl acetate:

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

Butan-1-ol:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

STOT - repeated exposure

Not classified based on available information.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Nickel:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Molybdenum:

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47.11 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr

n-Butyl acetate:

Species : Rat
NOAEL : 2.4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethyl acetate:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 3,600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 1.28 mg/l
LOAEL : 2.75 mg/kg
Application Route : inhalation (vapour)
Exposure time : 94 Days

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1,700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapour)
Exposure time : 8 Weeks

Ethylbenzene:

Species : Rat
LOAEL : 0.868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

Butan-1-ol:

Species : Rat
NOAEL : 125 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	: Rat
NOAEL	: >= 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 54 Days
Remarks	: Based on data from similar materials

Nickel:

Species	: Rat
NOAEL	: 4 mg/m3
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 412

Chromium:

Species	: Rat
NOAEL	: 1 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 28 Days
Method	: OECD Test Guideline 412
Remarks	: Based on data from similar materials

Molybdenum:

Species	: Rat
NOAEL	: 17 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23.2 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0.1 - < 1 mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 220 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,090 mg/l
Exposure time: 24 h
Method: DIN 38412

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1,650 mg/l
Exposure time: 0.25 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 9.65 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2.4 mg/l
Exposure time: 24 d
Species: Daphnia magna (Water flea)

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8,800 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 : 61,150 mg/l
Exposure time: 30 min
Method: ISO 8192

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 79 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Butan-1-ol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,328 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 4,390 mg/l
Exposure time: 17 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4.1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version 12.0 Revision Date: 30.04.2023 SDS Number: 9701550-00006 Date of last issue: 26.01.2023
Date of first issue: 21.12.2009

Nickel:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Chromium:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to fish (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 30 d
Species: Danio rerio (zebra fish)
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Aluminium:

Toxicity to fish : NOEC (Salmo trutta (brown trout)): > 80 µg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): > 0.135 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility

Molybdenum:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 609.1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 130.9 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (green algae)): 62.5 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (green algae)): 289.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 820 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: 200 mg/l
Exposure time: 32 d
Species: Oncorhynchus mykiss (rainbow trout)
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 50.8 mg/l
Exposure time: 21 d
Species: Ceriodaphnia dubia (water flea)

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Ethyl acetate:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %
Exposure time: 20 d

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Butan-1-ol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 20 d

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Nickel:

Biodegradability : Result: not rapidly degradable

12.3 Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.2

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2.3

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Ethyl acetate:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Bioconcentration factor (BCF): 30

Partition coefficient: n-octanol/water : log Pow: 0.68

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.6

Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1

Nickel:

Bioaccumulation : Bioconcentration factor (BCF): < 500
Remarks: Expert judgement

Molybdenum:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 4.9

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant) |
| Waste Code | : | The following Waste Codes are only suggestions:

used product
16 05 04, gases in pressure containers (including halons) containing hazardous substances

unused product
16 05 04, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances |

SECTION 14: Transport information

14.1 UN number

- | | | |
|------|---|---------|
| ADN | : | UN 1950 |
| ADR | : | UN 1950 |
| RID | : | UN 1950 |
| IMDG | : | UN 1950 |
| IATA | : | UN 1950 |

14.2 UN proper shipping name

- | | | |
|-----|---|----------|
| ADN | : | AEROSOLS |
| ADR | : | AEROSOLS |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN
Environmentally hazardous : no

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered: Nickel (Number on list 27)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Acetone

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)

P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t
-----	--------------------	---------------------	---------------------

Volatile organic compounds : Directive 2004/42/EC

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

VOC content in g/l: 690.3 g/l
Product sub-category: Special finishes
Coatings: All types
VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 88.7 %, 690.3 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H228 : Flammable solid.
H261 : In contact with water releases flammable gases.
H280 : Contains gas under pressure; may explode if heated.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer if inhaled.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H373 : May cause damage to organs through prolonged or repeated exposure.
H412 : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Flam. Sol.	:	Flammable solids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
Water-react.	:	Substances and mixtures, which in contact with water, emit flammable gases
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



STAINLESS STEEL SPRAY PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 26.01.2023
12.0	30.04.2023	9701550-00006	Date of first issue: 21.12.2009

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN